	SETUP	SI-		Г		
Name:		Date:		E	Event:	
City:	State:	Track:				
	□ Hard Packed □ Blue Groove □ Loose/Loamy □ Dry	UWet	Low BiteMed Bite	□ High Bite □ Other		
Front Suspension	Differentials		Ackerr	man	Bump Steer	
Toe:	- Front: Standard Smart		Long		Up Down	Lan
Ride Height:	Spring Wire Dia:		Shor	rt 💽	Op Down	4
Camber:	Qty of Springs:		(A)	Ā		$1 \xrightarrow{2}$
Caster:						
Sway Bar:	_ Grease:				r—Outsi	
Piston/Oil:	_ Diff Fluid:			B A		
Spring:	_			120		
Limiter/Droop:	- Center: Standard Small	rt	alat			
Overall Shock Length:	- Spring Wire Dia:				66	
Steering Ackerman:				M	A D B	
Bump Steer:	- Ramp Plate:			IL		
Camber Link:	-			5		
Shock Location:	0.0000		Notes:			
Receiver Battery Type:	_					
	-					
Rear Suspension						
Toe:						(Arg)
Anti-Squat:					4 <u> </u>	
Ride Height:					2 1	
Camber:					3	
Rear Hub Spacing:				РÇ В	A 2	
Sway Bar:					6	
Piston/Oil:				0000		
Spring:						
Limiter/Droop:					H	1
Overall Shock Length:			EN C			0
Camber Link:					09	U
Shock Location:					Inside	
Rear Diff Fluid:			e		Outside	
Engine			Notes:			
Engine:	_ Fuel:					
Glow Plug:	- Head Clearance:					
Pipe/Header:	_ Gearing:					
Clutch Clutch Shoes an	d Springs Info	Tires	Туре	(Compound	Insert
		Front:				
		Rear:				
		Notes: .				