



Name:		Date	e:			Event:	
City: State:		Tra	ck:				
	Hard Packed ☐ Blue Groove		Vet	□ Low Bite	☐ High Bite		
Conditions ☐ Outdoor ☐ Open ☐ Rough ☐			usty	☐ Med Bite			
Front Suspension	Differentials			Ackeri	man	Bump Steer	
Toe:	Front: Standard Smart	t	1	Lon	9	Q 5 Up Down	
Ride Height:	Spring Wire Dia			Sho	r (P)	Up Down	4
Camber:	Qty of Springs:		-	(9)			3
Caster:	Ramp Plate:			JP)	(IV		2
Spindle Height: □High □Low	Grease:						,
Wheel Hex:	Diff Fluid:		-				
Sway Bar:	Dili Fiulu.						3 (
Piston/Oil:	C						utside 4—08
Shock Type: □Bladder □Emulsion	Center: □Standard □Sm						
	Spring Wire Dia.:		-		A K	11	
Spring: Limiter/Droop:	Qty of Springs:						AM
	Ramp Plate:					1 68	
Overall Shock Length:	Grease:		-	\			_
Steering Ackerman:	Diff Fluid:						
Bump Steer:				A			
Camber Link:			N	otes:			
Shock Location:			_				
Receiver Battery Type:			-				· · · · · · · · · · · · · · · · · · ·
Poor Suspension			4 -				
Rear Suspension			VA	ing Setup			
Roll Center: □HRC □LRC							
Toe:				ing Type:	□2.0	I	
Anti-Squat:				ing Spacer		I	
Ride Height:			VV	icker Bill:	□.250	□.350	
Camber:						4	
Rear Hub Spacing:			-			2	
Wheel Hex:					DÇВА	1—	
Sway Bar: Piston/Oil:							
Shock Type: Bladder Emulsion							
Spring:				f	6000	Outside Inside	4 (1)
Limiter/Droop:			-				00
Overall Shock Length:			-				
Camber Link:			-			Jul Jul	
Shock Position:					6		(o) (o) 77022
Rear Diff Fluid:			_	9	1)
Engine Engine			- N	otes:			
			-				
	Fuel:		· -				
	Head Clearance		· -				
Pipe/Header:	Jeanny.						
Clutch Clutch Shoes and Springs Info Tire				Туре		Compound	Insert
Clutch Shoes and	Springs into	Tire:	_			•	
		ivot	.es: _				