Contains: Propane, butane, alcohols, dimethyl ether, pentane, acetates

Harmful if inhaled, may affect the brain or nervous system causing diziness, headache or nausea. Causes eye, skin, nose and throat irritation. Vapors may ignite explosively and accumulate readily. Do not puncture or incinerate container. Exposure to heat or prolonged exposure to sum may cause busing. Do not expose to heat or store at temperature above 120°f.

NOTICE: INTENTIONAL MISUSE BY DELIBERATELY Concentrating and inhaling the contents may be Harmful or fatal.

Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after use. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. Use with adequate ventilation. To avoid breathing woors and mist, one windows and toors or use means to ensure fresh air entry during application and dying.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water, get medical attention immediately. In case of skin contact, wash thoroughly with sapar and water. It swallowed, do not induce vomiting. Get medical attention immediately.





DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL IRRITANT. Refer to back panel. NET 5 oz. (150 ml)

FOR BEST RESULTS:

Bodies

ate

lvca

DO

for

1. Before use, shake the can vigorously for approximately 2 minutes after you hear the mixing ball rattle.

2. Spray at a distance of approximately 6 - 8 inches with an even back and forth motion.

3. Always spray one very light coat at a time. The final result is obtained after 3 - 5 coats. Wait approximately 5 minutes between coats. **Never spray just one heavy coat!**

 Allow the paint to dry for 5 minutes before applying the next coat and/or removing the masking film.

 For best results, use a small paint brush to apply 1-2 final finish coat(s) of ProGraphix® Black Acrylic Chrome Backing Paint (part #5044) to the body.

6. After use, turn the can upside down and spray for 2 seconds until the nozzle is empty.

KEEP OUT OF THE REACH OF CHILDREN

CONFORMS TO ASTM D-4236. For energency health information, call your Poison Control Center 1-800-222 -1222. WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Traxas, 6250 Traxas Way, McKinney, Texas 75070 USA Copyright © TRAXAS 2021 All rights reserved. Manufactured in Belgium. Distributed by TRAXAS, L.P. 1-888-TRAXAS (U.S. residents only). support@Traxas.com, www.Traxas.com