Contains: Propane, butane, alcohols, dimethyl ether, pentane, acetates

Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Vapors may ignite explosively and accumulate readily. Do not puncture or incinerate container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120°F.

NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after use. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. Use with adequate ventilation. To avoid breathing vapors and mist, open windows and doors or use means to ensure fresh air entry during application and drying.


First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. In case of skin contact, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Get medical attention immediately.











DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL IRRITANT. Refer to back panel.

NET 13.5 oz. (400 ml)

FOR BEST RESULTS:

- 1. Before use, shake the can vigorously for approximately 2 minutes after you hear the mixing ball rattle.
- 2. Spray at a distance of approximately 6 8 inches with an even back and forth motion.
- 3. Always spray one very light coat at a time. The final result is obtained after 3 5 coats. Wait approximately 5 minutes between coats. **Never spray just one heavy coat!**
- 4. Allow the paint to dry for 5 minutes before applying the next coat and/or removing the masking film.
- 5. For best results, use a small paint brush to apply 1-2 final finish coat(s) of ProGraphix® Black Acrylic Chrome Backing Paint (part #5044) to the body.
- 6. After use, turn the can upside down and spray for 2 seconds until the nozzle is empty.

KEEP OUT OF THE REACH OF CHILDREN

CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Traxxas, 6250 Traxxas Way, McKinney, Texas 75070 USA Copyright © TRAXXAS 2021 All rights reserved. Manufactured in Belgium. Distributed by TRAXXAS, L.P. 1-888-TRAXXAS (U.S. residents only). support@Traxxas.com, www.Traxxas.com