

## 1/16 Slash® 4X4 (Model 70054-8) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	7050	Half shafts, left or right (1/16 Slash)(internal splined half shaft (2)/external splined half shaft) (2))/ metal u-joints (4)
5124	Ball bearings, blue rubber sealed (4x7x2.5mm) (2)	7055	Rebuild kit (for 1/16 E-Revo/Slash steel constant-velocity
7019	Ball bearings, blue rubber sealed (4x8x3mm) (2)	1000	driveshafts) (includes pins, o-rings, stub axles for driveshafts
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)		assemblies)
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)	7054	Stub axle, steel (2)/ yokes (2) (assembled)
	Body & Accessories	7154	Wheel hubs, hex (4)/ axle pins (1.5x8mm) (4)
1926	Antenna caps, vinyl (2)/ antenna spool	7154X	Wheel hubs, hex, aluminum (4) (blue-anodized)
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	7057	Yokes, differential and transmission (2)/ 3x10mm screw pin (2)
1834	Body Clips (12) (standard size)		Front Suspension
7015	Body mounts, front & rear/ body mount posts, front & rear	7033X	Aluminum caps, pivot ball (threaded aluminum, hard-anodized,
4915	Body washers, foam adhesive (10)	70001	PTFE-coated (8)/ hex wrench, 5mm
6716	Body washers, Foam, 2mm/3mm/4mm	7034	Axle carriers, left & right (2 each)
7027X	Body, 1/16 Slash 4X4, ProGraphix® (graphics are printed,	7023	Bulkhead tie bars, front & rear (blue-anodized aluminum)/ 2.5x6 CS
	requires paint & final color application))/ decal sheet		(1)
7012R	Body, 1/16 Slash 4X4 (clear, requires painting)/ grille, lights decal sheet	7030X	Bulkhead, front (left & right halves)/ 3x10mm BCS (4)/ 2.5x23mm CS (1)
7027-BLK	Body, 1/16 Slash 4X4, black (painted, decals applied)	7028	Hollow balls (20)
7027-RED		7028X	Hollow balls, steel (machined) (22)
2514	Decal sheet, racing sponsors	7033	Pivot balls (4)/ pivot ball caps (4)
9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)	7018	Push rod (molded composite) (4)/ hollow balls (8) (1/16 Slash)
	Bumpers & Skidplates	7018X	Push rods, aluminum (red-anodized) (4) (assembled with rod
7005			ends) (1/16 Slash)
7035	Bumpers, front (1)/ rear (1)/ 2.5X14mm CS (2) (1/16 Slash)	7155	Rocker arm post, steel (4)
7037	Skidplate set, front (1)/ rear (1)/ transmission (1) (black)/ Guards,	7158	Rocker arm set, progressive-2/ 4x7x2.5mm PB (8)
	steering servo (2) / cover plate, steering servo (1)	2523	Screws, 2.5x10 countersunk machine (hex drive) (6)
	Chassis & Attachments	7043	Steering arm (upper & lower)/ steering link/ servo horn/ servo saver/
7015	Body mounts, front & rear/ body mount posts, front & rear		servo saver spring/ servo horn mount/ ball stud (2)/ shock mounts,
7024X	Box, receiver (sealed)/ wire cover/ foam pads, upper & lower/ silicone	<b>-</b> 004	front & rear/ 2.5x18mm CS (4)
	grease/ 2.5x8 CS (4)/ 3x4 GS (1)	7031	Suspension arm set, front (includes upper right & left and lower right
7023	Bulkhead tie bars, front & rear (blue-anodized aluminum)/ 2.5x6 CS	7004	& left arms)
	(1)	7021	Suspension pin set (front or rear), 2x46mm (2), 2x14mm (4)
7030X	Bulkhead, front (left & right halves)/ 3x10mm BCS (4)/ 2.5x23mm CS (1)	7038	Toe link, front & rear (molded composite) (4)/ hollow balls (8) (1/16 Slash)
7029X	Bulkhead, rear (left & right halves)/ 3x10mm BCS (4)/ 2.5x23mm CS (1)	7038X	Toe links, aluminum (red-anodized) (4) (assembled with rod ends and threaded inserts) (1/16 Slash)
7022	Chassis		Hardware
7026	Door, battery compartment (1)/ vents, battery compartment (1 pair)	5124	Ball bearings, blue rubber sealed (4x7x2.5mm) (2)
	(fits right or left side)	7019	Ball bearings, blue rubber sealed (4x8x3mm) (2)
7025	Seal kit, receiver box (includes o-ring, seals, and silicone grease)	7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)
7037	Skidplate set, front (1)/ rear (1)/ transmission (1) (black)/ Guards,	5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)
70.40	steering servo (2) / cover plate, steering servo (1)	5123	Bellcrank bushings (plastic) (4x7x2.5mm) (4)
7043	Steering arm (upper & lower)/ steering link/ servo horn/ servo saver/ servo saver spring/ servo horn mount/ ball stud (2)/ shock mounts,	1834	Body Clips (12) (standard size)
	front & rear/ 2.5x18mm CS (4)	2545	Bushings (plastic) (5x8x2.5mm) (4)
		5150	E-clips, 1.5mm (24)
	Differential Components	5477	Flat wrench, 5mm (blue anodized aluminum)
7019	Ball bearings, blue rubber sealed (4x8x3mm) (2)	7028	Hollow balls (20)
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)	7028X	Hollow balls, steel (machined) (22)
7080	Cover plates, differential (front or rear)/ gaskets (2)/ o-rings (2)/	2745	Nuts, 3mm nylon locking (12)
	2x14mm BCS (3)	1747P	Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4)
7078	Differential assembly, complete	3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)
7014	Differential kit, center (complete for 1/16 E-Revo, 1/16 Slash)	1747R	Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)
7381 5126¥	Differential locker, (2)	1747G	Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4)
<b>5136X</b> 7082	Differential oil kit (1 each: 10K, 30K, 50K weights) Gear set, differential (output gears (2)/ spider gears (3))/ differential	1747T	Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4)
1002	output shafts (2)/ 1.5x6mm pin (3)/ 1.5x8mm pin (2)	1747A	Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4)
5130	Oil, differential (100K wt) (0.7 oz (20cc))	7155	Rocker arm post, steel (4)
5130 5135	Oil, differential (10K wt) (1.7 oz (50cc))	7059	Rod ends (8)/ hollow balls (8) (fits 1/16 and 1/18 accessory
5136 5136	Oil, differential (30K wt) (1.7 oz (50cc))	2523	suspension links) Screws, 2.5x10 countersunk machine (hex drive) (6)
5137	Oil, differential (50K wt) (1.7 oz (50cc))	2523 3229	Screws, 2.5x10 countersunk machine (flex drive) (6) Screws, 2.5x10mm cap-head machine (hex drive) (6)
7014X	Rebuild kit, center differential (1/16 E-Revo/Slash) (includes o-	2526	Screws, 2.5x10mm cap-nead machine (nex drive) (6) Screws, 2.5x12 countersunk machine (hex drive) (6)
	rings and diff gear covers)	3236	Screws, 2.5x12 countersuit machine (fiex dive) (b)
7079	Ring gear, differential/ pinion gear, differential	3215	Screws, 2.5x6mm cap-head machine (by
	Driveline Components	3965	Screws, 2.5x8mm cap-head machine (6)
7024		2577	Screws, 3x10mm button-head machine (hex drive) (6)
7034 <b>7052</b>	Axle carriers, left & right (2 each)  Drive cups, inner (2) 1/16 E-Revo/Slash (steel constant-velocity	3159	Screws, 3x10mm caphead machine (hex drive) (6)/ lockwashers (6)/ hex wrench
7051	driveshafts) Driveshaft assembly (1) left or right (1/16 Slash) (fully assembled,	2578	Screws, 3x12mm button-head machine (hex drive) (6)
	ready to install)/ 3x10mm screw pin (1)	2579 2575	Screws, 3x15mm button-head machine (hex drive) (6)
7051X	Driveshaft, 1/16 Slash (steel constant-velocity) (assembled) (4)	2575	Screws, 3x6mm button-head machine (hex drive) (6)
7053	Driveshaft, steel constant-velocity, 1/16 Slash (shaft only,	2576	Screws, 3x8mm button-head machine (hex drive) (6)
	48mm)/ drive cup pin (1)	2743	Set (grub) screws, 3mm hardened (12)
=0=0=			Motors & Electronics
7250R	Driveshafts, center (steel constant-velocity) front (1), rear (1)		mutui 3 & Liggti viii 63
<b>7250R</b> 7056	(fully assembled) Half shafts, center front (1), center rear (1) (internal splined half shafts	2082A	Gear set (for 2080A waterproof micro servo)

Page 2  1/16 Slash® 4X4: Titan® 550 motor, TQ™ 2.4 radio (Model 70054-8) Parts Li	st
---	----

Heat simit, Verlineon® 300 brushless motor, aluminum (blue- motors) Motor must, finned aluminum (to 500 motors) Motor must, finned aluminum (to 500 motors) Motor must, finned aluminum (to 500 motors) Motor with the second aluminum (to 500 motors) Motor with th	Page 2	1/16 Slash® 4X4: Titan® 550 motor, TQ™ 2.4 radio	(Model 7	70054-8) Parts List
Motor mount, finned aluminum (5-50 moters) Motion mount, finned aluminum (5-50 moters) Motion mount, finned aluminum (5-50 moters) Motion, Tanno 127 (12-1 m., 300 dze) Servo, micro, waterproof, motion general	2082X 3374	Heat sink, Velineon® 380 brushless motor, aluminum (blue-		Traxxas® High Current Connector, NiMH only)
Motor mucus, finned aluminum (for 550 motors) Motor, Velinecon® Mini Maxxis 380, hreathest (passembled with Tod. Service, passembled with Motor Mini Maxxis 380, hreathest (passembled with Tod. Service, passembled with Motor, Velinecon® Mini Maxxis 380, hreathest (passembled with Tod. Service, passembled with Motor Mini Maxxis 380, hreathest (passembled with Tod. Service, passembled with Motor Mini Maxxis 380, hreathest (passembled with Tod. Service, passembled with Motor Mini Maxxis 380, hreathest (passembled with Tod. Service, passembled with Tod. Service, passembled,	7060	·	3024R	
Moder, (flamb LE) (LL) Lamp, 500 acids productions of the production of the producti				
1931 New York Control and Reduces Supplications (special control) and the state of Supplication of the Sup			70054-8	<u>-</u>
Servo case  gaskts  (for 2880X metal pasr, micro, waterproof servo, waterproof servo, waterproof servo, waterproof metal gaar		16-gauge wire and gold-plated connectors)	70004-0	2.4GHz radio
Servo   Serv		, ,	7022V	-
Servo, micro, waterproof, metal gear   2028   Servo, micro, waterproof,	20017		/U33A	
Servo, micro, waterproof, metal gear   370   Veilincendro WLL-3m Practises Power Systam, waterproof (includes waterproof VLL-3m ESC and Veilincendro 380 motor) (includes waterproof VLL-3m ESC and Veilincendro 380 motor)   370   375	2080A	•	7034	Axle carriers, left & right (2 each)
Velineon® VXL-3m Brushless Power System, waterproof (includes waterproof VXL-3m ESC and Valleneon® 389 motor)			7023	
(includes waterproof VXL-3 in ESC and Valence Orthor, waterproof (brushless) 3375			7029X	
No. 2 Piece control. Speed Control, waterproof With Low Voltage Delections   Relitio Systems Control, waterproof with Low Voltage Delections   Relitio Systems Relitations   Relitio Systems Relitations   Relitatio			. 020/	, , , , , , , , , , , , , , , , , , , ,
Delection  Bit III D YSIGIN Bit ICH ICS C PIRT ICH IS  Bit III D YSIGIN Bit ICH ICS C PIRT ICH IS  2200mah 7 A v 2-chil 23C LiPo Battery  Acapter, Traxxasi IDB LIPO battery (adapts Traxxasi IDB Lipo batteries to separate blance ports)  Battery charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Battery Charge indicators, green (d), grey (4), blue (4)  Charger, Dic. 2 amp (5 - 7 cell, 6 - 6 - 4 volt, NIMH I)  Charger, EZ-Pask Plus A, amp, NIMH/LIPo with ID Auto Battery Identification  Charger, EZ-Pask Plus A, amp, NIMH/LIPo with ID Auto Battery Identification  Charger, EZ-Pask Plus A, amp, NIMH/LIPo with ID Auto Battery Identification  Charger, EZ-Pask Plus A, amp, NIMH/LIPo with ID Auto Battery Identification  Battery Identification  Charger, EZ-Pask Plus A, amp, NIMH/LIPo with ID Auto Battery Identification  Battery Identification  Charger, EZ-Pask Plus A, amp, NIMH/LIPo with ID Auto Battery Identification  Battery Identification  Charger, EZ-Pask Plus A, amp, NIMH/LIPo with ID Auto Battery Identification  Battery Identification  Charger, LSP-Ca, 60W (6 - 7 cell, 7 - 2 - 8 a volt, NIMH/ (with ID®)  2989  Chapger, USB-C, 40W (6 - 7 cell, 7 - 2 - 8 a volt, NIMH/ (with ID®)  2989  Fuse, Dic. Charger, 8 (2) (for £3294, 22797)  2980  Fuse, Dic. Charger, 8 (2) (for £3294, 22797)  2980  Fuse, Dic. Charger, 8 (2) (for £3294, 22797)  2980  Fuse, Dic. Charger, 8 (2) (for £3294, 22797)  2980  Fuse, Dic. Charger, 8 (2) (for £3294, 22797)  2980  Fuse, Dic. Charger, 8 (2) (for £3294, 22797)  2980  Fuse, Dic. Charg	3375			` '
Push rod (molded composite) (4) follow balls (8) (1/16 Slash)   7018	3024R			
7918				
AC to DC adapter  Battery charge indicators, green (4), grey (4), blue (4)  Battery charge indicators, green (4), grey (4), blue (4)  Battery charge indicators, green (4), grey (4), blue (4)  Battery charge indicators, green (4), grey (4), blue (4)  Battery charge indicators, green (4), grey (4), blue (4)  Battery charge indicators, green (4), grey (4), blue (4)  Battery charge indicators  Charger, EZ-Peak Dual, 100W, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Dual, 100W, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 5, amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 5, amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with ID Auto Battery identification  Charger, LiB-C, 20W (5 - 7 call, 5 - 8 avolt, NiMH)  Charger, LiB-C, 20W (5 - 7 call, 5 - 8 avolt, NiMH)  Charger, LiB-C, 20W (6 - 7 call, 7 - 8 a avolt, NiMH)  Charger, LiB-C, 40W (6 - 7 call, 7 - 8 a avolt, NiMH)  Charger, LiB-C, 20W (7 - 7 call, 5 - 8 avolt, NiMH)  Charger, LiB-C, 20W (7 - 7 call, 5 - 8 avolt, NiMH)  Charger, LiB-C, 20W (7 - 7 call, 5 - 8 avolt, NiMH)  Charger, LiB-C, 20W (7 - 7 call, 5 - 8 avolt, NiMH)  Charger, LiB-C, 20W (7 - 7 call, 5 - 8 avolt, NiMH)  Charger, LiB-C, 20W (8 - 7 call, 7 - 8 avolt, NiMH)  Charger, LiB-C, 20W (8 - 7 call, 7 - 8 avolt, NiMH)  Charger, LiB-C, 20W (8 - 7 call, 7	2820Y			Push rods, aluminum (red-anodized) (4) (assembled with rod
Adapter, Traxxas@ ID® LiPo battery (edapts Traxxas@ ID® 1450 batteries to separate balance ports)  Battery charge indicators, green (4), grey (4), blue (4)  2423 Battery charge indicators, green (4), grey (4), blue (4)  2424 Battery charge indicators, green (4), grey (4), blue (4)  2424 Battery Charge (1), grey (4), blue (4)  2425 Battery Charge (1), grey (4), blue (4)  2426 Battery Charge (1), grey (4), blue (4)  2426 Battery Charge (1), grey (4), blue (4)  2427 Charger, EDRA Alkaline (4)  2428 Battery Charger, EDRA Alkaline (4)  2429 Charger, EDRA (1), green (1),	2976	•	7455	
Date in the superation during control of the property of the p	2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD®		
Battery   Coor, TO   2 4 transmitter (replacement for #6516, 6517 transmitter)	20.42	• • • •		· · ·
### stansmitter) ### st			7043	Steering arm (upper & lower)/ steering link/ servo horn/ servo save
Battery, Power Cell AA Alkalane (4)				servo saver spring/ servo horn mount/ ball stud (2)/ shock mounts, front & rear/ 2 5x18mm CS (4)
Saltery, Serices   Prower Cell, 1, 20 Undahn (NiMH, etc.) tat. (1, 24), 248	2914	• • • • • • • • • • • • • • • • • • • •	7032	` '
Charger, EZ-Peak Dual, 100W, NIMH/LiPo with iD Auto Battery Identification				
Identification   Sizeh   No.   No.		• , , , , , , , , , , , , , , , , , , ,		
Battery Identification  Charger, EZ-Peak Plus 4, amp, NiMH/LIPo with ID Auto Battery Identification  B		Identification		Slash)
Charger, EZ-Peak® Plus 4s, 8 amp, NIMHLIPo with ID® Auto	2970		70368	and threaded inserts) (1/16 Slash)
Battery   Identification	0004			
Charger, LE2-PeakA®, USB-C, 40W, NiMM+(JiPo with IbA® Auto	2981			
Battery Identification	2985			
Charger, USB-C, 40W (6 - 7 cell, 7.2 - 8.4 volt, NIMH) (with ID®) 20787 Fuse, D/C charger, SA (2) for #12974, 2975, 2977) 20787 Gear set (for 2080A waterproof micro servo) 20788 Gear set (for 2080A waterproof micro servo) 20789 Gear set, metal (for 2080X waterproof micro servo) 20789 LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® ID® batteries) 20789 LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® ID® batteries) 20789 Mount, temperature sensor (electric motors)/ wire tie/ thermal pad 207912 Power adapter, AC, USB-C, 45W) 207916 Power cable, USB-C, 45W) 207917 Receiver, micro, TQ 2.4GHz (3-channel) 207918 Receiver, micro, TQ 1.4GHz (3-channel) 207918 Receiver, micro, TQ 1.4GHz (3-channel) 207919 Receiver, micro, TQ 1.4GHz (3-channel) 207910 Servo case/ gaskets (for 2080X metal gear, micro, waterproof servo) 207019 Servo, micro, waterproof, metal gear 207019 Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1) 207017 Tansmitter, TQ 1.4GHz, 2-channel (transmitter, 5-ch micro receiver) 207018 Traxmas® Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207018 Traxmas® Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz high output, 2-channel (transmitter only) 207019 Traxmasw Link enabled, 2.4GHz hig	00.40			
Fuse, D/C charger, SA (2) (for #2974, 2975, 2977)  Gear set (for 2080A waterproof micro servo)  Gear set, metal (for 2080R waterproof micro servo)  Traxxas® ID® batteries)  6538  LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® ID® batteries)  6539  6535  Munt, temperature sensor (electric motors)/ wire tie/ thermal pad  2912  2916  Power adapter, AC, USB-C (45W)  7028  2916  Power cable, USB-C, 100W (high output)  7087  Receiver, micro, TQ 2.4.GHz (3-channel)  5638  Receiver, micro, TQ 12.4.GHz with telemetry & TSM® (5-channel)  5639  Servo case/ gaskets (for 2080A micro waterproof servo)  Servo case/ gaskets (for 2080A micro waterproof servo)  Servo, micro, waterproof, metal gear  Toll 2.4 GHz High Output radio system, 4-channel with Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)  Transmiter, TQ 2.4.GHz, 2-channel (transmitter only)  Transmiter, TQ 2.4.GHz, 2-channel (transmitter)  Transmiter, TQ 2.4.GHz high output, 2-channel (transmitter only)  Transmiter, TQ 1.7. Traxxas® Link enabled, 2.4.GHz high output, 2-channel (transmitter only)  Transmiter, TQ 2.4.GHz high output  Traxxas® Link Bluetooth® module  Traxxas® Link Bluetooth module  T				
2082A Gear set, metal (for 2080K waterproof micro servo) 2082X Gaar set, metal (for 2080K waterproof micro servo) 2082X Gaar set, metal (for 2080K waterproof micro servo) 2082X LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® fib® batteries) 2086 LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® fib® batteries) 2087 Mount, temperature sensor (electric motors)/ wire tie/ thermal pad 2088 Power adapter, AC, USB-C (45W) 2081 Power adapter, AC, USB-C (45W) 2081 Receiver, micro, TO 2.4GHz (3-channel) 20812 Sensor, RPM (short)/ 3x4mm BCS (1)/ 3x4 GS (1) 20813 Sensor, temperature and voltage (short) 20814 Servo case/ gaskets (for 2080K metal gear wire) 20800 Servo, micro, waterproof servo) 20800 Servo, micro, waterproof, metal gear 20800 Servo, micro, vaterproof, metal gear 20800 Servo, micro, waterproof, metal gear 20800 Servo, micro, vaterproof, metal gear 20800 Servo, micr	2978			
Gars set, metal (for 2080X waterproof micro servo) LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® (ib® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® (ib® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® (ib® batteries)  Mount, temperature sensor (electric motors)/ wire tie/ thermal pad  2912 Power adapter, AC, USB-C (45W) 2916 Power cable, USB-C, 100W (high output) 6519 Receiver, micro, TQ 2.4GHz (3-channel) 6522 Sensor, RPM (short)/1 3x4mm BCS (1) 3x4 GS (1) 6523 Sensor, RPM (short)/1 3x4mm BCS (1) 3x4 GS (1) 6524 Servo case/ gaskets (for 2080X metal gear, micro, waterproof servo) 2080X Servo, micro, waterproof, metal gear 2080X Servo, micro, water	2082A			
LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® iD® cell voltage checker/balancer (2) doubleds; plot voltage checker/balancer (2) for Comparisor (2) for Comparisor (2) for Comparisor (2) for Comparisor (2)		·	5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt,
Traxxas® ID® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® ID® batteries) Mount, temperature sensor (electric motors)/ wire tie/ thermal pad adapter. AC, USB-C (45W) Power cable, USB-C, 100W (high output) Power cable, USB-C, 400W (high output) Power cable, USB-C, 100W (high output) Power cable, USB-C, 100W (high output) Power cable, USB-C, 100W (high output) Power cab			E038	
Traxxas® ID® batteries)  Traxxas® ID® batteries)  Mount, temperature sensor (electric motors)/ wire tie/ thermal pad  2912 Power adapter, AC, USB-C (45W)  Power cable, USB-C, 100W (high output)  86519 Receiver, micro, TQ 2.4GHz (3-channel)  86522 Sensor, RPM (short)/ 3x4mm BCS (1)/ 3x4 GS (1)  20814 Servo case/ gaskets (for 2080A micro waterproof servo)  2080A Servo, micro, waterproof, metal gear  2080X Servo, micro, waterproof, metal gear  2080A Servo, micro, waterproof, metal gear  2080B Servo, micro, waterproof, metal gear  2080A Servo, micro, waterproof, metal gear  2080B Servo, micro, waterproof, metal gear  2080B Servo, micro, waterproof, metal gear  2080B Servo, micro, waterproof, metal gear  2080C Servo, micro, waterproof, metal gear  2080B Servo, micro, waterproof, metal gear  2080C Servo, micr		` ` '	3030	
Mount, temperature sensor (electric motors)/ wire tie/ thermal pad Power adapter, AC, USB-C (45W) Power adapter, AC, USB-C (45W) Power able, USB-C, 100W (high output) Power able, USB-C	2968		7066	
Power adapter, AC, USB-C (45W) Power cable, USB-C, 100W (high output) Power cable, USB-C, 100W (high output) Power cable, USB-C, 100W (high output) Piston, damper (2x0.5mm hole, red) (4/) travel limitlers (4) Piston, damper (2x0.5mm hole, red) (4/) travel limiters (4) Piston, damper (2x0.5mm hole, red) (4/) travel limiters (4) Piston, damper (2x0.5mm hole, red) (4/) travel limiters (4) Piston, damper (2x0.5mm hole, red) (4/) travel limiters (4) Piston, damper (2x0.5mm hole, red) (4/) travel limiters (4) Piston, damp	6535	·		Caps and spring retainers, GTR shock (upper cap (2)/ hollow balls
Power cable, USB-C, 100W (high output) Receiver, micro, TO 2.4GHz (3-channel) Receiver, micro, TQ 2.4GHz (3-channel) Serso, RPM (short)/ 3x4mm BCS (1)/ 3x4 GS (1) Receiver, micro, TQ 2.4GHz (3-channel) Receiver, m		•	7000	() ()
Receiver, micro, TQ 2.4GHz (3-channel)  Receiver, micro, TQ 12.4GHz with telemetry & TSM® (5-channel)  Receiver, micro, TQ 12.4GHz with telemetry & TSM® (5-channel)  Sensor, RPM (short)/ 3x4m BCS (1)/ 3x4 GS (1)  Sensor, temperature and voltage (short)  Servo case/ gaskets (for 2080A micro waterproof servo)  Servo, micro, waterproof, metal gear, micro, waterproof servo, micro, waterproof, metal gear  Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) 3x1		• • • •		, ,
Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel) Sensor, RPM (short)/ 3x4mm BCS (1)/ 3x4 GS (1) Sensor, temperature and voltage (short) Servo case/ gaskets (for 2080A micro waterproof servo) Servo, case/ gaskets (for 2080X metal gear, micro, waterproof servo) Servo, micro, waterproof, metal gear Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger ma		· · · · · · · · · · · · · · · · · · ·		
Sensor, temperature and voltage (short) Servo case/ gaskets (for 2080A micro waterproof servo) Servo case/ gaskets (for 2080X metal gear, micro, waterproof servo) Servo, micro, waterproof, metal gear Slipper clutch, complete (includes slipper clutch hub, clutch pad, spring, 3.0mm NL, 1.5x6mm pin)  Spring, shock (GTR) (0.82 rate, double dran) (1 pair) Spring, shock (GTR) (1.02 rate, double dran) (1 pair) Spring, shock (GTR) (1.15 rate, double dran) (1 pair) Spring, shock (GTR) (1.15 rate, double dan) (1 pair) Spring, shock (GTR) (1.15 rate, double dran) (1 pair				clips, shock rod ends, hollow balls) (renews 2 shocks)
Servo case/ gaskets (for 2080A micro waterproof servo)  Servo case/ gaskets (for 2080X metal gear, micro, waterproof servo)  Servo, micro, waterproof  Servo, micro, waterproof, metal gear  Servo, micro, waterproof, metal gear  Servo, micro, waterproof, metal gear  Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/3x8mm CCS (3)/3x10mm CCS (3)  Telemetry trigger magnet, 5x2mm (1)/3x8mm CCS (3)/3x10mm CCS (3)  Telemetry trigger magnet, 5x2mm (1)/3x8mm CCS (3)/3x10mm CCS (3)  Tol; 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)  Tol; 2.4 GHz High Output radio system, 4-channel with Traxxas® Link enabled, TSM® (4-ch transmitter, 5-ch micro receiver)  Transmitter, Tol; Traxxas® Link enabled, 2.4GHz high output, 2-channel (transmitter only)  Transmitter, Tol; Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, Tol; Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, Tol; Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Traxass® Link Bluetooth® module  Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Traxxas® Link Bluetooth® module  Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Traxxas® Link Bluetooth® module				
Servo case/ gaskets (for 2080X metal gear, micro, waterproof servo)  Servo, micro, waterproof  Servo, micro, waterproof, metal gear  Siliper clutch, complete (includes slipper clutch hub, clutch pad, spring, 3.0mm NL, 1.5x6mm pin)  Spring, 3.0mm NL, 1.5x6mm pin)  Spring, shock (GTR) (0.82 rate, double green) (1 pair)  Spring, shock (GTR) (0.82 rate, double green) (1 pair)  Spring, shock (GTR) (0.82 rate, double green) (1 pair)  Spring, shock (GTR) (1.15 rate, double black) (1 pair)  Spring, shock (GTR) (1.15 rate, double black) (1 pair)  Spring, shock (GTR) (1.15 rate, double dank) (1 pair)  Spring, shock (GTR) (1.15 rate, double dank) (1 pair)  Spring, shock (GTR) (1.15 rate, double dank) (1 pair)  Spring, shock (GTR) (1.15 rate, double dank) (1 pair)  Spring, shock (GTR) (1.15 rate, double dank) (1 pair)  Spring, shock (GTR) (1.15 rate, double dank) (1 p				
Servo, micro, waterproof  2080R Servo, micro, waterproof, metal gear  2080R Spring, shock (GTR) (0.82 rate, double orange) (1 pair)  2080R Spring, shock (GTR) (0.82 rate, double droof, 1 pair)  2080R Spring, shock (GTR) (0.82 rate, double droof, 1 pair)  2080R Spring, shock (GTR) (0.82 rate, double droof, 1 pair)  2080R Spring, shock (GTR) (1.15 rate, double droof, 1 pair)  2080R Spring, shock (GTR) (1.15 rate, double droof, 1 pair)  2080R Spring, shock (GTR		, ,		• • • • • • • • • • • • • • • • • • • •
Servo, micro, waterproof, metal gear Servo, micro, waterproof, metal gear Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5X2mm (1) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQ 2.4GHz, 2-channel (transmitter only) Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only) Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only) Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only) Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only) Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only) Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only) Traxxas® Link Bluetooth® module Traxxas® Link Bluetooth® module VXL-3m Electronic Speed Control, waterproof (brushless)  Slipper clutch, complete (includes slipper clutch hub, clutch pad, spring, 3.0mm NL, 1.5x6mm pin) Slipper clutch, complete (includes slipper clutch hub, clutch pad, spring, 3.0mm NL, 1.5x6mm pin) Slipper clutch, complete (includes slipper clutch hub, clutch pad, spring, 3.0mm NL, 1.5x6mm pin) Spring, 3.0mm NL, 1.5x6mm pin)  Spring, 3.0mm NL, 1.5x6mm pin)  Spring, shock (GTR) (0.82 rate, double orange) (1 pair) Spring, shock (GTR) (1.02 rate, double drange) Spring, shock (GTR) (0.82 rate, double orange) (1 pair) Spring, shock (GTR) (1.02 rate, double drange) Spring, 3.0mm NL, 1.5x6mm pin)  Spring, 3.0mn NL, 1.5x6mm pin  (GTR) (0.2 rate, double dra		servo)	7061X	Shocks, GTR hard anodized, PTFE-coated bodies with TiN sha (fully assembled, without springs) (4)
Servo, micro, waterproof, metal gear Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3)  Telemetry trigger magnet, 5x2mm (1) Telemetry trigger magnet, 5x2mm (1)  Tol. 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)  Tol. 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)  Transmitter, TQ 2.4GHz, 2-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4GHz high output, 2-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQ irraxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Gear, 18-T pinion (48-pitch) / set screw  Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw				
Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/ 3x8mm CCS (3)/ 3x10mm CCS (3)  Telemetry trigger magnet, 5X2mm (1)  Tilemetry trigger magnet, 5X2mm (1)  Spring, 3.0mm NL, 1.5x6mm pin)  Spring, 3.0mm NL, 1.5x6mm pin 1.5ml pin in 1.5ml pi	2080X	Servo, micro, waterproof, metal gear	7152	
Fig. 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)  TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Tink Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)  Transmitter, TQ 2.4 GHz, 2-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 3-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 3-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 3-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 3-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 4-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 4-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 4-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 4-channel (transmitter only)  Transmitter, TQ 1 Traxxas® Link enabled, 2.4 GHz high output, 4-channel (transmitter only)  Traxas® Link Bluetooth® module  Traxxas® Link Bluetooth® module  Traxxas® Link Bluetooth® module  VXL-3m Electronic Speed Control, waterproof (brushless)	6538	, , , , , , , , , , , , , , , , , , , ,	7 102	spring, 3.0mm NL, 1.5x6mm pin)
enabled, TSM® (2-ch transmitter, 5-ch micro receiver)  TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)  Transmitter, TQ 2.4GHz, 2-channel (transmitter only)  Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 2-channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Traxsas® Link Bluetooth® module  Traxxas® Link Bluetooth® module  VXL-3m Electronic Speed Control, waterproof (brushless)  Tiping, shock (GTR) (1.02 rate, double green) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double tan) (1 pair)  Spring, shock (GTR) (1.02 rate, double ta	6540		74.40	
TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)  Transmitter, TQ 2.4GHz, 2-channel (transmitter only)  Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQ i Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Traxxas® Link Bluetooth® module  Traxxas® Link Bluetooth® module  VXL-3m Electronic Speed Control, waterproof (brushless)  Traxxas® Link Bluetooth® module  Traxxas® Link Bluetooth® module  VXL-3m Electronic Speed Control, waterproof (brushless)  Traxxas® Link Bluetooth® module  Traxxas® Link Bluetooth® module  VXL-3m Electronic Speed Control, waterproof (brushless)  Traxxas® Link Bluetooth® module	NEUCO			
Transmitter, TQ 2.4GHz, 2-channel (transmitter only)  Transmitter, TQ 1.4GHz, 2-channel (transmitter only)  Transmitter, TQ 1.4GHz, 2-channel (transmitter only)  Transmitter, TQ 1.7 pinion (48-pitch) (fits 3mm shaft)/ set screw channel (transmitter only)  Transmitter, TQ 1.7 pinion (48-pitch) / set screw Gear, 19-T pinion (48-pitch) / set screw Gear, 19-T pinion (48-pitch) / set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear,	5507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas®	7142	Spring, shock (GTR) (1.02 rate, double tan) (1 pair)
Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only)  Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)  Traxxas® Link Bluetooth® module	2546	•		
channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)  Traxxas® Link Bluetooth® module  Traxxas® Link Bluetooth® module  VXL-3m Electronic Speed Control, waterproof (brushless)  2416  Gear, 16-T pinion (48-pitch) / set screw  Gear, 19-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw  Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw			2428	-
Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only)  Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)  Traxxas® Link Bluetooth® module  VXL-3m Electronic Speed Control, waterproof (brushless)  Traxxas® Link enabled, 2.4GHz high output, 4- 2423 Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw	0340			
Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- 2423 Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw channel (transmitter only) 2426 Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw 6511 Traxxas® Link Bluetooth® module 4728 Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw 7428 VXL-3m Electronic Speed Control, waterproof (brushless) 2431 Gear, 31-T pinion (48-pitch) (fits 3mm shaft)/ set screw 6431	6529	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-	1918	Gear, 18-T pinion (48-pitch) / set screw
channel (transmitter only)  2426 Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw  4728 Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw  4728 Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw  4728 Gear, 31-T pinion (48-pitch) (fits 3mm shaft)/ set screw  4728 Gear, 31-T pinion (48-pitch) (fits 3mm shaft)/ set screw	0500	` <del>*</del> '		
6511 Traxxas® Link Bluetooth® module 4728 Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw 3375 VXL-3m Electronic Speed Control, waterproof (brushless) 2431 Gear, 31-T pinion (48-pitch) (fits 3mm shaft)/ set screw	<b>6530</b>			
3375 VXL-3m Electronic Speed Control, waterproof (brushless) 2431 Gear, 31-T pinion (48-pitch) (fits 3mm shaft)/ set screw	6511	` <del>*</del> '		
4725 Gear, pinion (25-tooth) (48-pitch) / set screw	3375			

7045R	Spur gear, 45-tooth	8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"
7046R <b>7047R</b>	Spur gear, 50-tooth Spur gear, 55-tooth	8716X	drive Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
704710	Steering Components		3.0mm) 1/4" drive
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
2545	Bushings (plastic) (5x8x2.5mm) (4)	8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
7043	Steering arm (upper & lower)/ steering link/ servo horn/ servo saver/ servo saver spring/ servo horn mount/ ball stud (2)/ shock mounts,	0744	2.5mm, 3.0mm), 1/4" drive
	front & rear/ 2.5x18mm CS (4)	8714	Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1 Phillips, and #2 Phillips bits), 1/4" drive
7038	Toe link, front & rear (molded composite) (4)/ hollow balls (8) (1/16	2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench /
7038X	Slash) Toe links, aluminum (red-anodized) (4) (assembled with rod ends		2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
	and threaded inserts) (1/16 Slash)	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
	Suspension Linkage		3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips,
7028	Hollow balls (20)		#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm
<b>7028X</b> 7018	Hollow balls, steel (machined) (22)		wrenches/ driver handle)
7018X	Push rod (molded composite) (4)/ hollow balls (8) (1/16 Slash)  Push rods, aluminum (red-anodized) (4) (assembled with rod		Turnbuckles & Threaded Rods
	ends) (1/16 Slash)	7028	Hollow balls (20)
7021	Suspension pin set (front or rear), 2x46mm (2), 2x14mm (4) Toe link, front & rear (molded composite) (4)/ hollow balls (8) (1/16	<b>7028X</b> 7018	Hollow balls, steel (machined) (22) Push rod (molded composite) (4)/ hollow balls (8) (1/16 Slash)
7038	Slash)	7018X	Push rods, aluminum (red-anodized) (4) (assembled with rod
7038X	Toe links, aluminum (red-anodized) (4) (assembled with rod ends		ends) (1/16 Slash)
	and threaded inserts) (1/16 Slash)	7038	Toe link, front & rear (molded composite) (4)/ hollow balls (8) (1/16 Slash)
	Tires & Wheels	7038X	Toe links, aluminum (red-anodized) (4) (assembled with rod ends
7073A	Tires & wheels, assembled, glued (SCT satin chrome wheels, red beadlock style, SCT off-road racing tires, foam inserts) (1 each, right		and threaded inserts) (1/16 Slash)
	& left)		
7073	Tires & wheels, assembled, glued (SCT satin chrome wheels, SCT		
7071	off-road racing tires, foam inserts) (1 each, right & left) Tires, off-road racing, SCT dual profile (1 each right & left)/ foam		
	inserts (2)		
7154	Wheel hubs, hex (4)/ axle pins (1.5x8mm) (4)		
<b>7154X</b> 7072A	Wheel hubs, hex, aluminum (4) (blue-anodized) Wheels, SCT satin chrome, red beadlock style, dual profile (1.8"		
	inner, 1.4" outer) (2)		If you have questions or need technical assistance, call Traxxas at:
	Transmission Components		1-888-TRAXXAS
7077R	Cover, gear/ motor mount hinge post/ 3x10mm CS with split and		(1-888-872-9927) (U.S. residents only)
7379R	flat washers (1)/ 3x8mm BCS (1) Cover, gear/motor plate access cover/ motor mount hinge post /		For orders, calls outside the U.S., and other information, call 972-549-3000,
70751	3x10mm CS w/split and flat washers (1) / 2.5x4mm CS (2) / 3x8mm		or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com
<b>7044</b>	BCS (1) (for 550 motors)		TRAXXAS.LUM
<b>7014</b> 7093	Differential kit, center (complete for 1/16 E-Revo, 1/16 Slash) Gear set, transmission (includes 18T, 25T input gears, 13T idler gear		
	(steel), 35T output gear, M3x13.75 screw pin)		
7091	Gearbox halves, front & rear		
7092 <b>7090</b>	Input shaft/ output shaft  Plate, motor		
7380	Plate, motor (for 550 motor)		
7014X	Rebuild kit, center differential (1/16 E-Revo/Slash) (includes o-		
7152	rings and diff gear covers) Slipper clutch, complete (includes slipper clutch hub, clutch pad,		
	spring, 3.0mm NL, 1.5x6mm pin)		
7095	Transmission, complete (fits 1/16-scale brushed models)		
	Traxxas Tools		
3433X	Body reamer (aluminum handle)		
3433 3436	Body reamer (plastic handle) Cap, body reamer		
3432	Scissors, curved tip		
3431	Scissors, straight tip		
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight:		
	1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,		
	and 8.0mm), 1/4" drive		

and 8.0mm), 1/4" drive

8.0mm), 1/4" drive

Speed bit handle, large (overmolded) Speed bit handle, medium (one piece)

Speed bit handle, premium (rubber overmold)

5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive

Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm,

Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive

Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,

8720

8721 8722

8710

8711

8719